# IRONERS

TFI 6026 · 6032



#### STANDARD FEATURES & BENEFITS

- · Ergonomic cylinder heated ironer
- · Gas or electric heating
- · Extended heat transfer path
- $\cdot$  Large surface contact with linen
- · Roll standard with chrome surface coating for better thermal conduction and highly resistant to corrosion, even after periods of inactivity
- $\cdot\,$  Finger protection panel and emergency button for more safety
- · Easy to use electronic control with pre-set ironing programmes
- $\cdot$  Indication of ironing temperature and speed
- · Frequency controlled motor
- · Reverse mode possible
- $\cdot$  Space-saving wall model with front return of the linen
- $\cdot\,$  Overheating check system with 2 temperature sensors
- · Premix burner for more power and efficient ironing
- $\cdot$  LED lights on the ironing width for good visibility and operation

#### **OPTIONS**

- · Longitudinal fold
- · 3 folding sensors at feeding point instead of 1
- · Transport wheels
- · Rear output of the linen



## **IRONERS**

### TFI 6026 · 6032

MODEL	UNIT	TFI 6026	TFI 6032	
Roll diameter	in	23.62	23.62	
Working width	in	102.3	126	
Roll speed	in/min	0.137-0.472	0.137-0.472	
Performance* Electric folding	lb/h	319-357	397-441	
HEATING				
Electric				
Electric heating power **	kW	56	69	
Evaporation	gal/h	17	21	
Electric consumption	kW/h	57.8	71	
Gas				
Gas heating power	kW	65	80	
dus ricuting power	Btu	221789	272971	
Evaporation	gal/h	21.1	26.4	
	DN/BSP			
Gas connection Ø		20 (¾")	20 (¾")	
Gas pressure	psi	0.30-0.87	0.30-0.87	
Gas consumption	kW/h	56	84	
VOLTACE/ELECTRIC CONNECT	Btu/h	190350	287320	
VOLTAGE/ELECTRIC CONNECT	ION			
Electric				
		380-415V 3ph + N 50Hz		
		380-415V 3ph + N 60Hz 440-480V 3ph 50Hz		
		440-480\	/ 3ph 60Hz	
Gas				
		380-415V 3ph + N 50Hz 380-415V 3ph + N 60Hz 440-480V 3ph 50Hz 440-480V 3phN 60Hz		
		200-240V 3ph 50Hz 200-240V 3ph 60Hz 200-240V 1ph 50/60Hz		
MOTORS				
Roll motor	hp	1.019	1.019	
Fan motor	hp	1.49	1.49	
EXHAUST				
Exhaust connection Ø	in	4.92	4.92	
Airflow				
Electric	ft³/h	39729	39729	
Gas	ft³/h	39729	39729	
DIMENSIONS (WxDxH)				
Standard	in	139.8 x 53.18 x 62.91	163.46 x 53.18 x 62.91	
Standard rear exit model	in	139.8 x 64.84 x 62.91	163.46 x 64.84 x 62.91	
Packed	in	143.7 x 59 x 69.21	167.32 x 59 x 69.21	
Packed rear exit model	in	143.7 x 70.87 x 69.21	167.32 x 70.87 x 69.21	
WEIGHT	III	143.7 × 70.07 × 03.21	107.32 \ 70.07 \ 03.21	
	lb	4023	4431	
Net				
Gross	lb	4354	4894	
SOUND LEVEL	db(A)		2.CE C	
	db(A)	< 65.6	< 65.6	

 $<sup>\</sup>star$  50% moisture - folding at 0.354 in/min



<sup>\*\*</sup> Output calculated at 380V/IIIphase